

Material Safety Data Sheet

2008.01.28

1. Chemical Product and Company Identification

Product Name: PPS Resin RS-1340 Black

Chemical Name: Polyphenylene Sulfide

Manufacturer: Kotec Corporation

Address: 21-15, 3-Cho, Chayamadai, Sakai, Osaka, 590-0115 Japan

Phone Number: +81-722-94-8711 (Emergency)

Fax Number: +81-722-94-8533

E-Mail: info@kotec-corp.co.jp

2. Composition / Information on Ingredients

Chemical / Mixture: Mixture

Ingredients	CAS No.	Wt.%
PPS	26125-40-6	≥ 59
Glass fiber	65997-17-3	40
Carbon Black	1333-86-4	≤ 1

3. Hazards Identification

The most important hazards and effects: None

Skin contact: Essentially non-irritating to skin

Eye contact: Solid or powder may cause irritation by an abrasive action of solid or powder.

Inhalation: PPS resin under normal processing temperatures (330°C - 330°C) releases very little gases, which has a irritation property. However, if the temperature exceeds 360°C, decomposition will occur rapidly and release of carbon oxides, sulfur dioxide occurred resulting in acute lethality.

Ingestion: Oral toxicity is very low.

Environmental effects: None

Physical and chemical hazards: Not applicable

Specific hazards: Not applicable

4. First Aid Measures

Skin contact: Flush the skin with running water. For skin contact with fume condensation, immediately wash the affected area thoroughly with soap and water. For skin contact with molten plastic, immediately cool with water and seek medical attention.

Eye contact: Immediately irrigate the affected eye(s) with clean water for at least 15 minutes. Do not rub eye(s) to prevent irritation and damages to cornea(s). If irritation develops or persists, obtain medical attention.

Inhalation: Remove the victim from the area to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical attention if any breathing difficulty persists.

Ingestion: Not a likely route of exposure. If swallowed, seek medical attention.

Note: Several thermal burns can result from contact with molten immediately

5. Fire-Fighting Measures

Extinguishing media: Water spray, dry chemical, chemical foam, and carbon dioxide.

Hazardous Combustion Products: This material is a combustible thermoplastic, which will melt and drip when ignited and give combustion products.

Fire Fighting: Firefighters should wear protective clothing and use self-contained breathing apparatus when fighting fire involving this material.

Explosive: Not explosive.

6. Accidental Release Measures

Personal precautions: Pellets spilled on the floor can cause slipping.

Environmental precautions: PPS resin is a stable organic thermoplastic and a hazardous polymerization will not occur.

Recovery: To prevent the danger of slipping or falling, sweep up or vacuum the spilled materials and place them in a proper waste container for disposal.

7. Handling and Storage

Handling: Always wear recommended personal protective equipment. Wash thoroughly after handling. Launder contaminated clothing before reuse. Long retention at high temperature can cause heat decomposition. Spilled pellets on a floor can cause a slip.

Prevention of user exposure: Gases generated in the moulding process may cause irritation to the skin and respiratory tract. Avoid dust or pellets in contact with eyes. Do not touch molten resin to prevent a burn.

Prevention of fire and explosion: PPS resin will not ignite itself at normal temperature but keep fire away wherever and whenever possible.

Measures to prevent dust generation: Use local exhaust ventilation. Avoid breathing thermal processing fume vapor.

Storage: PPS resin will not degrade during storage. While heating and/or cooling is not required, the resin should be stored indoor to protect it from rain or excessive moisture. Periodically check storage for vertical stability and/or container damage or fatigue. Store resin in clean, dry environment in sealed containers. Avoid storing flammable materials in the resin storage area.

8. Exposure Controls / Personal Protection

ACGIH – None listed

OSHA – None listed

Engineering controls: Thermal processing equipment should be ventilated to control gas and fume given off when the resin is heated to extrusion or injection molding temperatures. For most operations, a continuous supply of fresh air to the general workplace area along with the continuous removal of processing fume contaminated air through a local exhaust ventilation system will be adequate. However, the ventilation requirements must be determined on an individual basis for each workplace.

Eye protection: Wear safety glasses with side shields or chemical safety goggles as described by OSHA's eye and face protection regulations.

Skin and body Protection: None required in normal handling of pellets. When handling the hot resin (extruded, air shots or parts), well-insulated gloves are to be worn to prevent thermal burns.

Respiratory Protection: None required in normal handling of pellets. In handling of resins that may be reinforced with fiberglass, it may be necessary to wear a NIOSH / MSHA approved dust respirator if the airborne dust concentration is near or exceeds the nuisance dust.

Ingestion: No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

9. Physical and Chemical Properties (SI unit)

Appearance: Pellets

Physical State: Solid

Flash Point: Over 500 °C

Melting point: 280°C

Boiling point: Not available

Vapor Pressure: Not available

Specific Gravity: 1.66

Solubility: Insoluble in water

Upper flame limit: Not available

Lower flame limit: Not available

10. Stability and Reactivity

Stability: Stable under normal temperatures and pressures.

Reactivity: Not reactive under recommended conditions of handling, storage, processing and use.

Conditions to avoid: Incompatible materials, dust generation, strong oxidants.

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Carbon monoxide, carbon dioxide, sulfur dioxide, Irritating and toxic fumes, smoke and fume.

Hazardous Polymerization: Has not been reported

Storage stability: Stable

Reactivity in water: None

Oxidizing property: None

Self-reactivity / Potential for explosion: None

11. Toxicological information

Acute inhalation: Processing fumes from similar materials are not considered toxic. There were no distinct or consistent treatment related tissue or organ changes noted in gross necropsies.

Acute toxicity: No data available

Sensitization and chronic toxicity: No data available

12. Ecological Information

The material, which is resistant to biodegradation and insoluble in water, is expected to present any ecologically significant problems and not considered degradable or toxic in terms of their physical impact. Pellets left at large (spills) in the general environment may be ingested by animals. Do not dispose any of the material into marine or water area to prevent marine animals or birds from ingestion.

13. Disposal Considerations

Comply with all applicable national and local laws or regulations. Do not dispose into sewers, ground or body of water. Preferred options for disposal are recycle, incineration with energy recovery and landfill. Remove all packaging for recovery or waste disposal.

14. Transport Information

Comply with all applicable national and local laws or regulations. Avoid water and careless handling to prevent damage to the container. Watch your step not to slip in the event that pellets spill out of the torn container.

International regulations for transport: US DOT - Not applicable

IMO - Not applicable

IATA - Not applicable

RID/ADR - Not applicable

Canadian TDG - Not applicable

15. Regulatory Information

Comply with all national and local regulations.

16. Miscellaneous Information

Disclaimer: The information set forth herein is offered as a service to our customers and is not intended to relieve a customer from its responsibility to determine the suitability of this information or of the materials described herein for purchaser's purpose; to investigate other sources of information; to comply with all laws and procedures regarding safe use of these materials; and to use these materials in a safe manner. Although this information is believed to be accurate, Kotec Corporation specifically disclaims responsibility for any liability of any kind arising from any party's use of or reliance on information or recommendations set forth herein. No warranty of any kind shall be construed to arise by implication from any information or recommendation contained herein. This document may be revised by new knowledge.